

Pyroplex

Fire Rated Expanding Foam



750ml
Hand Held
PFRF750A



750ml
Gun Application
PFRF750GUN



Pyroplex Flame retardant based polyurethane expanding foam for sealing gaps around door frames or perimeter pointing. Expands up to 38 times its volume. Suitable for use on FD30, FD60, FD90 and FD120 doorsets. Pyroplex fire rated expanding foam will achieve a fire resistance period of up to 120 minutes.

Performance and Certification: Fire – BS EN 1366-4 | Certifire TS40 Certificate CF828

Test Standard

- Fire – BS EN 1366-4 | Certifire TS40 Certificate CF828

Features

- Fire resistance of up to 2 hours dependent upon gap to depth ratio.
- Quick curing, can be cut, sawn or formed within 60 minutes of application.
- Easy to install, with up to 3m linear joint being fitted in under 10 minutes.
- Can be painted and/or plastered without additional primers.
- Expands up to 38 times its volume.

Material

- Flame retardant based polyurethane.

Supplied

- 750ml Hand held and gun application.
- Available in pink foam.
Other colours are available on special request.

Application

Pyroplex Fire Rated Expanding Foam is suitable for use in a wide range of construction and building fire stopping solutions.

Health and safety

- Store between 5°C and 30°C in unopened condition
Do not expose to frost.
- Use in well ventilated areas



Pyroplex

Fire Rated Expanding Foam | Installation Instructions



750ml
Hand Held
PFRF750A



750ml
Gun Application
PFRF750GUN

Pyroplex Flame retardant based polyurethane expanding foam for sealing gaps around door frames or perimeter pointing.

Performance and Certification: Fire – BS EN 1366-4 | Certifire TS40 Certificate CF828

Installation instructions

Preparation of the substrate:

- 1.0 Surfaces must be firm, clean, free of dust and loose particles. The cavity or voided area to be filled must be well moistened with water, this will aid installation adhesion to the substrate. It may be necessary to use a primer, prior to the application of the foam.
- 2.0 It is important to use the foam within a temperature controlled environment, the minimum temperature to which the foam can be installed should be no less than +20°C.
- 3.0 If the temperature is below +20°C, the foam may show signs of slumping and irregular expansion.
- 4.0 Cans should not be left in an over-heated environment, temperatures above +50°C or exposed to direct sunlight.
- 5.0 Prior to application, ensure that the surrounding area is protected, in particular when using the foam in retrofit applications. It may also be necessary to mask and protect the surrounding area of the cavity, particularly in areas where the compartment may be decorated or furnished.
- 6.0 Shake the can for two minutes, until the foam inside becomes liquid. This is essential to ensure the performance of the product. Then attach the adapter or gun to the canister.
- 7.0 Fill the cavity from the base of the aperture slowly and build up the layers of the foam, ensuring that the void is filled. Take care not to over-fill the cavity.

- 8.0 Allow the foam to cure and using a sharp bladed instrument, cut-off the expanded 'cured' foam.

- 9.0 Ensure that empty cans are disposed of by reference to local regulations.

Specification Overview

Characteristics	Appearance – result
750ml canister	Approximately 38 litres
Cell structure	Medium fine in appearance
Tack time	6 to 12 mins, dependent upon environmental conditions
Tool time [cutting]	Under 30 mins, dependent upon environmental conditions
Full stability load bearing [20mm bead]	After approximately 12 hours
Tensile strength TM108 [dry surface]	18N/cm ²
Elongation @ tension TM108 [dry surface]	18%
Shear strength TM1012 [moistened surface]	>40 kPa
Thermal conductivity [EN12667]	0.03W/mk

Maintenance and installation records

Pyroplex Limited recommend that all firestopping materials are checked on a regular basis to ensure that the product remains integral.

Product guarantee

Providing the product is installed in accordance with the requirements of the guidance document, the fire performance characteristics of the product is guaranteed for a period of 10 years.



Fire Rated Expanding Foam | Material Safety Datasheet

Section 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier:** PFRF750GUN/PFRF750A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:** Relevant uses: Foam.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Pyroplex Limited, The Furlong, Droitwich, Worcestershire, WR9 9BG, United Kingdom
Phone: +44 (0)1905 795432 | email: info@pyroplex.com | www.pyroplex.com
E-mail of competent person responsible for SDS: andy.walsh@pyroplex.com
- 1.4 Emergency telephone number:** +44 (0)1905 795432

Section 2: Hazards identification

- 2.1.1 Classification of the substance or mixture:**
CLP Regulation (EC) n° 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.
Aerosol 1: Flammable aerosols, Category 1, H222
Aerosol 1: Pressurised container: May burst if heated., H229
Aquatic Chronic 4: Hazardous to the aquatic environment, long-term hazard, Category 4, H413
Carc. 2: Carcinogenicity, Category 2, H351
Eye Irrit. 2: Eye irritation, Category 2, H319
Lact.: Reproductive toxicity, effects on or via lactation, H362
Resp. Sens. 1: Sensitisation, respiratory, Category 1, H334
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1: Sensitisation, skin, Category 1, H317
STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:

CLP Regulation (EC) n° 1272/2008:

Danger



Hazard statements:

- Aerosol 1:** H222 - Extremely flammable aerosol
Aerosol 1: H229 - Pressurised container: May burst if heated
Aquatic Chronic 4: H413 - May cause long lasting harmful effects to aquatic life
Carc. 2: H351 - Suspected of causing cancer
Eye Irrit. 2: H319 - Causes serious eye irritation
Lact.: H362 - May cause harm to breast-fed children
Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
Skin Irrit. 2: H315 - Causes skin irritation
Skin Sens. 1: H317 - May cause an allergic skin reaction
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure
STOT SE 3: H335 - May cause respiratory irritation

Precautionary statements:

- P101:** If medical advice is needed, have product container or label at hand
P102: Keep out of reach of children
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211: Do not spray on an open flame or other ignition source

P251: Do not pierce or burn, even after use

P302+P352: IF ON SKIN: Wash with plenty of water

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F

P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

Supplementary information:

EUH204: Contains isocyanates. May produce an allergic reaction.

Additional Labelling (Annex XVII, REACH):

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards: Non-applicable.

Section 3: Composition / Information on ingredients

3.1 Substance: Non-applicable.

3.2 Mixture:

Chemical description: Mixture composed of polyurethane in solvents.

Components: In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

Identification		Chemical name/Classification		Concentration
CAS: 9016-87-9 EC: Non-applicable Index: 615-005-00-9 REACH: Non-applicable	4,4'-methylenediphenyl diisocyanate, isomers and homologues		ATP ATP01	30 - <50 %
	Regulation 1272/2008	Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335 - Danger.	 	
CAS: 75-28-5 EC: 200-857-2 Index: 601-004-00-0 REACH: 01-2119485395-27-XXXX	Isobutane		ATP CLP00	10 - <20 %
	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger		
CAS: 85535-85-9 EC: 287-477-0 Index: 602-095-00-X REACH: 01-2119519269-33-XXXX	Alkanes, C14-17, chloro		ATP ATP01	10 - <20 %
	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Lact.: H362 - Warning THE PURPOSE OF THE INGREDIENT: FILLER/PLASTICIZER. LEVEL OF CONTENT IN THE FORMULA: 15-20 %. THE CURED PRODUCT CONTAINS SUBSTANCE ALKANES, C14-17, CHLORO, BUT MIGRATION OF SUBSTANCE FROM THE PRODUCT IS NOT TO BE FORESEEN.		
CAS: 115-10-6 EC: 204-065-8 Index: 603-019-00-8 REACH: 01-2119472128-37-XXXX	Dimethyl ether		ATP CLP00	2,5 - <5 %
	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger		
CAS: 13674-84-5 EC: 237-158-7 Index: Non-applicable REACH: 01-2119480419-30-XXXX	Tris(1-chloro-2-propyl) Phosphate		Self-classified	2,5 - <5 %
	Regulation 1272/2008	Acute Tox. 4: H302 - Warning		
CAS: 74-98-6 EC: 200-827-9 Index: 601-003-00-5 REACH: 01-2119486944-21-XXXX	Propane		ATP CLP00	1 - <2,5 %
	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger		
CAS: 106-97-8 EC: 203-448-7 Index: 601-004-00-0 REACH: 01-2119474691-32-XXXX	Butane		ATP CLP00	1 - <2,5 %
	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger		
CAS: 6425-39-4 EC: 229-194-7 Index: Non-applicable REACH: 01-2119969278-20-XXXX	2,2'-dimorpholinyl-diethyl ether		Self-classified	0,1 - <1 %
	Regulation 1272/2008	Eye Irrit. 2: H319 - Warning		

Section 4: First aid measures

4.1 Description of first aid measures

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact: Remove uncured foam using a piece of cloth and an unaggressive solvent, e.g. ethanol. Wash your hands and the cleaned skin surface using soapy water. Cured foam can be removed mechanically with the use of a brush, soap and plenty of water. Use protective cream after skin surface has been cleaned.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed: No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed: No further relevant information available.

Section 5: Fire fighting measures

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

Section 7: Handling and storage

7.1 Precautions for safe handling:

A: – Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B: – Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C. – Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D. – Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A. – Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

B. – General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Field of application of the product is described in Technical data sheet (TDS).

Section 8: Exposure controls / Personal protection

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental Limits		
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	IOELV (8h)	1000 ppm	1920 mg/m ³
	IOELV (STEL)		
	Year	2015	

Identification		Short Exposure		Long Exposure	
		Systemic	Local	Systemic	Local
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	47.9 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	6.7 mg/m ³	Non-applicable
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1894 mg/m ³	Non-applicable

Identification		Short Exposure		Long Exposure	
		Systemic	Local	Systemic	Local
2,2'-dimorpholinyl-diethyl ether CAS: 6425-39-4 EC: 229-194-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	7.28 mg/m ³	Non-applicable

Identification		Short Exposure		Long Exposure	
		Systemic	Local	Systemic	Local
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	Oral	Non-applicable	Non-applicable	0.58 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	28.75 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2 mg/m ³	Non-applicable
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	471 mg/m ³	Non-applicable
2,2'-dimorpholinyl-diethyl ether CAS: 6425-39-4 EC: 229-194-7	Oral	Non-applicable	Non-applicable	0.5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1.8 mg/m ³	Non-applicable

Identification				
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	STP	80 mg/L	Fresh water	0.001 mg/L
	Soil	11.9 mg/kg	Marine water	0.0002 mg/L
	Intermittent	Non-applicable	Sediment (Fresh water)	13 mg/kg
	Oral	10 g/kg	Sediment (Marine water)	2.6 mg/kg
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	STP	160 mg/L	Fresh water	0.155 mg/L
	Soil	0.045 mg/kg	Marine water	0.016 mg/L
	Intermittent	1.549 mg/L	Sediment (Fresh water)	0.681 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.069 mg/kg
Tris(1-chloro-2-propyl) Phosphate CAS: 13674-84-5 EC: 237-158-7	STP	Non-applicable	Fresh water	0.42 mg/L
	Soil	1.33 mg/kg	Marine water	0.42 mg/L
	Intermittent	Non-applicable	Sediment (Fresh water)	2.96 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	2.96 mg/kg
2,2'-dimorpholinyl-diethyl ether CAS: 6425-39-4 EC: 229-194-7	STP	100 mg/L	Fresh water	0.1 mg/L
	Soil	1.58 mg/kg	Marine water	0.01 mg/L
	Intermittent	1 mg/L	Sediment (Fresh water)	8.2 mg/kg
	Oral	10 g/kg	Sediment (Marine water)	0.82 mg/kg

8.2

Exposure controls:

A. – General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the professional exposure limits. In case of using individual protection equipment they should have the CE marking in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B. – Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 <p>Mandatory respiratory tract protection</p>	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2001+A1:2009	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C. – Specific protection for the hands.

Pictogram	PPE	Labelling	CEN Standard	Remarks
 <p>Mandatory hand protection</p>	NON-disposable chemical protective gloves		EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

D. – Ocular and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 <p>Mandatory face protection</p>	Face mask		EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E. – Bodily protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 <p>Mandatory complete body protection</p>	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 <p>Mandatory complete body protection</p>	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EEN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006	Replace boots at any sign of deterioration.

F. – Additional emergency measures

It is not necessary to take additional emergency measures.

Emergency Measure	Standards	Emergency Measure	Remarks
 <p>Emergency shower</p>	ANSI Z358-1 ISO 3864-1:2002	 <p>Eyewash station</p>	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	19.53 % weight
V.O.C. density at 20 °C:	Non-applicable
Average carbon number:	Non-applicable
Average molecular weight:	Non-applicable

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Aerosol

Appearance: Non-applicable

Color: Non-applicable

Odor: Non-applicable

Volatility:

Boiling point at atmospheric pressure: -25 °C (Propellant)

Vapour pressure at 20 °C: Non-applicable *

Vapour pressure at 50 °C: Non-applicable *

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: Non-applicable *

Relative density at 20 °C: Non-applicable *

Dynamic viscosity at 20 °C: Non-applicable *

Kinematic viscosity at 20 °C: Non-applicable *

Kinematic viscosity at 40 °C: Non-applicable *

Concentration: Non-applicable *

pH: Non-applicable *

Vapour density at 20 °C: Non-applicable *

Partition coefficient n-octanol/water 20 °C: Non-applicable *

Solubility in water at 20 °C: Non-applicable *

Solubility properties: Non-applicable *

Decomposition temperature: Non-applicable *

Melting point/freezing point: Non-applicable *

Recipient pressure: Non-applicable *

Explosive properties: Non-applicable *

Oxidising properties: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

Flammability:

Flash Point: -41 °C (Propellant)

Autoignition temperature: 240 °C (Propellant)

Lower flammability limit: Non-applicable *

Upper flammability limit: Non-applicable *

9.2 Other information:

Surface tension at 20 °C: Non-applicable *

Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

Section 10: Stability and reactivity

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact and air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

Section II: Toxicological information**11.1 Information on toxicological effects:**

Contains glycols. With possibility of effects that are hazardous to the health, it is recommended not to breathe the vapours for long periods of time.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A. – Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B. – Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C. – Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D. – CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: May cause harm to breast-fed children

E. – Sensitizing effects:

- Respiratory: Prolonged exposure can result in specific respiratory hypersensitivity.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F. – Specific target organ toxicity (STOT) – single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G. – Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H. – Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute Toxicity		Genus
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	308.5 mg/L (4 h)	Rat
Isobutane CAS: 75-28-5 EC: 200-857-2	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L (4 h)	
Butane CAS: 106-97-8 EC: 203-448-7	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	658 mg/L (4 h)	Rat
Propane CAS: 74-98-6 EC: 200-827-9	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L (4 h)	
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: Non-applicable	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	11 mg/L (4 h) (ATEI)	
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L (4 h)	
Tris(1-chloro-2-propyl) Phosphate CAS: 13674-84-5 EC: 237-158-7	LD50 oral	632 mg/kg	Rat
	LD50 dermal	2000 mg/kg	Rabbit
	LC50 inhalation	11 mg/L (4 h)	Rat
2,2'-dimorpholinylethyl ether CAS: 6425-39-4 EC: 229-194-7	LD50 oral	2025 mg/kg	Rat
	LD50 dermal	3038 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	

Section 12: Ecological information

Contains phosphates. Excessive discharge may cause eutrophication.

12.1 Toxicity:

Identification	Acute Toxicity		Species	Genus
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	LC50	0.1 - 1 mg/L (96 h)		Fish
	EC50	0.1 - 1 mg/L		Crustacean
	EC50	0.1 - 1 mg/L		Algae

Aquatic toxicity test data on the mixture (One-Component Foam (OCF1) containing 20% Mid Chained Chlorinated Paraffin (CAS 85535-85-9)):

ErC50 (Desmodesmus subspicatus) >1000 mg/l (72 h)

NOErC (Desmodesmus subspicatus) ≥1000 mg/l (72 h)

EC50 (Daphnia magna) >1000 mg/l (24 and 48 h)

NOEC (Daphnia magna) ≥1000 mg/l (24 and 48 h)

12.2 Persistence and degradability:

Identification	Acute Toxicity		Species	Genus
Tris(1-chloro-2-propyl) Phosphate CAS: 13674-84-5 EC: 237-158-7	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0%

12.3 Bioaccumulative potential:

Identification	Acute Toxicity	
Isobutane CAS: 75-28-5 EC: 200-857-2	BCF	27
	Pow Log	2.76
	Potential	Low
Tris(1-chloro-2-propyl) Phosphate CAS: 13674-84-5 EC: 237-158-7	BCF	5
	Pow Log	2.59
	Potential	Low
Propane CAS: 74-98-6 EC: 200-827-9	BCF	13
	Pow Log	2.86
	Potential	Low
Butane CAS: 106-97-8 EC: 203-448-7	BCF	33
	Pow Log	2.89
	Potential	Moderate
2,2'-dimorpholinyl-diethyl ether CAS: 6425-39-4 EC: 229-194-7	BCF	3
	Pow Log	
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Isobutane CAS: 75-28-5 EC: 200-857-2	Koc	35	Henry	1.206E+5 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	9.84E-3 N/m (25 °C)	Moist soil	Yes
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	1.136E-2 N/m (25 °C)	Moist soil	Non-applicable
Propane CAS: 74-98-6 EC: 200-827-9	Koc	460	Henry	7.164E+4 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	7.02E-3 N/m (25 °C)	Moist soil	Yes
Butane CAS: 106-97-8 EC: 203-448-7	Koc	900	Henry	9.626E+4 Pa·m ³ /mol
	Conclusion	Low	Dry soil	Yes
	Surface tension	1.187E-2 N/m (25 °C)	Moist soil	Yes
2,2'-dimorpholinyl-diethyl ether CAS: 6425-39-4 EC: 229-194-7	Koc	786	Henry	2E-9 Pa·m ³ /mol
	Conclusion	Low	Dry soil	No
	Surface tension	Non-applicable	Moist soil	No

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

Section 13: Disposal considerations**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	Gases in pressure containers (including halons) containing dangerous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP4 Irritant – skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising, HP7 Carcinogenic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with

Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated.

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

Section 14: Transport information

Transport of dangerous goods by land:	With regard to ADR 2015 and RID 2015:	
	14.1 UN number:	UN1950
	14.2 UN proper shipping name:	AEROSOLS, flammable
	14.3 Transport hazard class(es):	2
	Labels:	2.1
	14.4 Packing group:	N/A
	14.5 Dangerous for the environment:	No
	14.6 Special precautions for user	
	Special regulations:	190, 327, 344, 625
	Tunnel restriction code:	D
	Physico-Chemical properties:	see section 9
	Limited quantities:	1 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:		Non-applicable
Transport of dangerous goods by sea:	With regard to IMDG 37-14:	
	14.1 UN number:	UN1950
	14.2 UN proper shipping name:	AEROSOLS, flammable
	14.3 Transport hazard class(es):	2
	Labels:	2.1
	14.4 Packing group:	N/A
	14.5 Dangerous for the environment:	No
	14.6 Special precautions for user	
	Special regulations:	190, 277, 327, 344, 63, 959
	EmS Codes:	F-D, S-U
	Physico-Chemical properties:	see section 9
	Limited quantities:	1 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:		Non-applicable
Transport of dangerous goods by air:	With regard to IATA/ICAO 2015:	
	14.1 UN number:	UN1950
	14.2 UN proper shipping name:	AEROSOLS, flammable
	14.3 Transport hazard class(es):	2
	Labels:	2.1
	14.4 Packing group:	N/A
	14.5 Dangerous for the environment:	No
	14.6 Special precautions for user	
	Physico-Chemical properties:	see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:		Non-applicable

Section 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**
 Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
 Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable
 Article 95, REGULATION (EU) No 528/2012: Non-applicable
 REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable
- Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):**
 Contains more than 0.1 % of 4,4'-methylenediphenyl diisocyanate, isomers and homologues by weight. This product may not be distributed in its present form for first-time sale to the general public after 27th December 2010 unless the packaging contains protective gloves meeting the provisions of European Council Directive 89/686/CEE.
- Specific provisions in terms of protecting people or the environment:**
 It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.
- Other legislation:**
 The product could be affected by sectorial legislation
 Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers
 Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers
 Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers
 Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures.
- 15.2 Chemical safety assessment:**
 The supplier has not carried out evaluation of chemical safety.

Section 16: Other information

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EU) N° 453/2010, Regulation (EC) N° 2015/830)

Modifications related to the previous security card which concerns the ways of managing risks:

CLP Regulation (EC) n° 1272/2008:

· Hazard statements

Texts of the legislative phrases mentioned in section 2:

H222: Extremely flammable aerosol

H315: Causes skin irritation

H319: Causes serious eye irritation

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled

H317: May cause an allergic skin reaction

H351: Suspected of causing cancer

H362: May cause harm to breast-fed children

H335: May cause respiratory irritation

H373: May cause damage to organs through prolonged or repeated exposure

H413: May cause long lasting harmful effects to aquatic life

H229: Pressurised container: May burst if heated

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) n° 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed

Acute Tox. 4: H332 - Harmful if inhaled

Aquatic Acute 1: H400 - Very toxic to aquatic life

Aquatic Chronic 1: H410 – Very toxic to aquatic life with long lasting effects
 Carc. 2: H351 – Suspected of causing cancer
 Eye Irrit. 2: H319 – Causes serious eye irritation
 Flam. Gas 1: H220 – Extremely flammable gas
 Lact.: H362 – May cause harm to breast-fed children
 Press. Gas: H280 – Contains gas under pressure, may explode if heated
 Resp. Sens. 1: H334 – May cause allergy or asthma symptoms or breathing difficulties if inhaled
 Skin Irrit. 2: H315 – Causes skin irritation
 Skin Sens. 1: H317 – May cause an allergic skin reaction

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://esis.jrc.ec.europa.eu>

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol–water partition coefficient

Koc: Partition coefficient of organic carbon

Other information:

Classification procedure:

Acute Tox. 4: Calculation method

Aerosol 1: Calculation method

Aerosol 1: Calculation method

Carc. 2: Calculation method

Eye Irrit. 2: Calculation method

Lact.: Calculation method

Resp. Sens. 1: Calculation method

Skin Irrit. 2: Calculation method

Skin Sens. 1: Calculation method

STOT RE 2: Calculation method

STOT SE 3: Calculation method

Aquatic Chronic 4: Test data (FEICA Position Paper on the classification and labelling of One-Component Foam (OCFI) containing Mid Chained Chlorinated Paraffin (MCCP). (17.03.2015))

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.