



## Intumescent Acrylic Sealant



310ml Sealant Tube 2WT310PY



600ml Foil Pack 2SWT600



10 Litre Tub 2WT10LPY



Pyroplex® Intumescent Acrylic Sealant is a one-part high modulus, halogen free material. The product is designed for use in internal application. It is suitable for perimeter pointing around services and for use in low movement linear joints in walls and floors. Pyroplex Intumescent Acrylic Sealant can provide up to 240 minutes fire resistance integrity depending on application and backing material required. The material is compatible with common building materials.

**Performance and Certification:** Fire – BS 476: Part 20/22 | Fire – BS EN 1366-4 | IFC Certificate No. IFCC1366

### Test Standard

- BS 476: Part 20/22 | BS EN 1366-4 | IFC Certificate No. IFCC1366

### Features

- Fire resistance up to 4 hours (240 minutes)
- Excellent adhesion with common building materials
- Movement capability  $\leq 7.5\%$
- Cartridges and foil packs are fully recyclable
- Internal use only

### Material

- A water-borne acrylic sealant with fire and smoke resisting capability for internal gap sealing

### Supplied

- 310 ml cartridges, 600 ml foil pack or 10 Litre tubs

### Glazing Beads

- Available in white. Other colours are available on request

### Application

Pyroplex® Intumescent Acrylic Sealant has been designed for:

- Sealing linear gap joint seals up to 40mm width
- Sealing around plastic pipe or cable penetrations which have been protected with the recommended Pyroplex intumescent product eg. CE Marked Pipe Collar, CE Marked Pipe Wrap

### Health and safety

- Store between 5°C and 30°C in unopened condition  
Do not expose to frost
- Use in well ventilated areas
- Tools can be cleaned with soap and water







## Intumescent Acrylic Sealant | Installation Instructions



310ml Sealant Tube 2WT310PY



600ml Foil Pack 2SWT600



10 Litre Tub 2WT10LPY

Pyroplex® Intumescent Acrylic Sealant is a water-borne acrylic sealant with fire and smoke resisting capability for internal gap sealing. The product is designed for use in internal application. It is suitable for perimeter pointing around services and for use in low movement linear joints in walls and floors. **Performance and Certification:** Fire – BS 476: Part 20/22 | Fire – BS EN 1366-4 | IFC Certificate No. IFCC1366

### Installation instructions

- 1.0 For internal applications ensure that all the surfaces are clean, dry, sound and frost free. Clean all joints thoroughly to ensure that the adhesion of the acrylic to the substrate is not impaired.
- 2.0 It may be necessary to mask adjacent areas to prevent contamination and to ensure a neat sealant line. Masking tapes should be immediately removed after tooling and finishing.
- 3.0 Install backing materials as required and fill the cavity with acrylic.
- 4.0 The joint should be tooled within 5 minutes of application to ensure a good contact between the acrylic and substrate. Tooling of the sealant also gives a smooth and professional finish.
- 5.0 Dispose of spent cartridges in accordance with local regulations.

### Product testing

A number of independent fire resistance tests have been carried out to confirm the suitability of the product and to demonstrate product compliance by utilising BS EN 1366-4 and other international standards.

Pyroplex® Intumescent Acrylic Sealant has a European Classification EI 240 in accordance with BS EN 13501-2.

For applications in terms of linear joint details and fire performance this information is contained within the IFCC certification, and classification reports. (Available on our website to download at [www.pyroplex.com](http://www.pyroplex.com))

### Consumption guide

Depth	Width			
	6mm	10mm	15mm	20mm
6mm	8m	5m	3m	2m
10mm	5m	3m	2m	1m
15mm	3m	2m	1m	1m

Linear metres per 310ml cartridge, the figures quoted estimated and for guidance only.

### Maintenance and installation records

Pyroplex Limited recommend that all firestopping materials are checked on a regular basis to ensure that the product remains integral.

### Product guarantee

Providing the product is installed in accordance with the requirements of the guidance document, the fire performance characteristics of the product is guaranteed for a period of 10 years.



## Intumescent Acrylic Sealant | Material Safety Datasheet

### Section 1: Identification of the substance / Mixture and of the company

- 1.1 Product name:** Pyroplex intumescent acrylic
- 1.2 Use:** A water-borne acrylic sealant with fire and smoke resisting capability for internal gap sealing.
- 1.3 Supplier of the safety data sheet:**  
Pyroplex Limited, The Furlong, Droitwich, Worcestershire, WR9 9BG, United Kingdom  
Phone: +44 (0)1905 795432 | email: info@pyroplex.com | www.pyroplex.com  
**E-mail of competent person responsible for SDS:** andy.walsh@pyroplex.com
- 1.4 Emergency telephone number:** +44 (0)1905 795432

### Section 2: Hazards identification

- 2.1.1** Regulation ec 1272/2008  
This product is not classified as hazardous according to regulation (ec) 1272/2008 (clp)
- 2.2 Label elements**
- 2.2.1** Regulation ec 1272/2008  
**Signal word:** None  
**Hazard statement:** None
- 2.3 Other hazards**

### Section 3: Composition / Information on ingredients

Ingredient	CAS No.	EC No.	REACH Registration No.	Classification According to Reg. (EC) 1278/2008 (CLP)	% W/W
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	6846-50-0	229-934-9	01-2119451093-47-0000	H412	5-10%

### Section 4: First aid measures

- 4.1 General:** In all cases of doubt or when symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.  
**Skin contact:** Wash skin thoroughly with soap and water or a recognised skin cleaner.  
Do not use solvent or thinners.  
**Eye contact:** Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes holding eyelids apart, and seek medical advice.  
**Ingestion:** If accidentally swallowed wash mouth with water and give water to drink. Do not induce vomiting.  
**Inhalation:** Remove to fresh air.
- 4.2 Most important symptoms and effects**  
**Skin contact:** No symptoms anticipated  
**Eye contact:** There may be irritation and redness  
**Ingestion:** No symptoms anticipated. If there is any persistence of discomfort seek medical advice  
**Inhalation:** No symptoms

### Section 5: Fire fighting measures

- The liquid product is 'non-flammable'.
- 5.1 Extinguishing media:** Recommended: alcohol resistant foam, co2, powder, water spray/mist.
- 5.2 Special hazards:** As the products contain combustible organic components, fire will produce hazardous products of combustion (see section 10).  
Exposure to decomposition products may be a hazard to health.
- 5.3 Advice for firefighters:** Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray.  
Do not allow run off from fire fighting to enter drains or water courses.

## Section 6: Accidental release measures

- 6.1 Personal precautions and protective equipment:** refer to section 8 of sds for details
- 6.2 Environmental precautions:** Do not allow to enter drains or water courses. If the product enters drains or sewers, the local water company should be contacted immediately. In the case of contamination of streams, rivers or lakes, the relevant environment agency.
- 6.3 Method for containment and clean up:** Contain and collect spillages with non-combustible absorbent materials e.g. Sand, earth, vermiculite, diatomaceous earth, and place in a suitable container for disposal in accordance with the waste regulations (see section 13).

## Section 7: Handling and storage

- 7.1 Precautions for safe handling:** Avoid contact with skin and eyes. Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection see section 8.
- The manual handling operations regulations:** May apply to the handling of containers/packages of this product. In order to calculate the weight of any pack size, multiply the volume in litres by the specific gravity value given in section 9. This will give the net weight of the product in kilograms.
- 7.2 Precautions for safe storage:** Keep containers closed when not in use. Never use high pressure to empty. The container is not a pressure vessel. Ensure good housekeeping and regular safe removal of waste materials. Observe label precautions – store between 5°C and 25°C in a dry well-ventilated place away from sources of heat. Protect from frost. Keep out of reach of children. Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

## Section 8: Exposure controls / Personal protection

**Engineering measures:** Provide adequate ventilation during application and drying. Where practicable this should be achieved by the use of local exhaust ventilation. If this is not sufficient to maintain concentration of solvent vapours below the relevant occupational exposure limit, suitable respiratory protection must be worn (see 'occupational exposure controls' below).

### Exposure limits:

Substance	Occupational Exposure Limits				Notations
	8 hr LTEL (1)		15 min STEL(2)		
	ppm	mgm-3	ppm	mgm-3	

- (1) Long-term exposure limit – 8 hour time weighted average.  
 (2) Short-term exposure limit – 15 mins time weighted average.  
 (S) Occupational exposure standard (oes)  
 (m) Maximum exposure limit (mel)  
 (r) Recommended by suppliers  
 (a) Allocated limits by analogy with similar materials  
 (sk) Risk of absorption through unbroken skin  
 (sen) Capable of causing sensitisation by inhalation

**Occupational exposure controls:** All personal protective equipment (ppe), including respiratory protective equipment (rpe), used to control exposure to hazardous substances must be selected to meet the requirements of the coshh regulations.

**Respiratory protection:** If exposure to hazardous substances identified in section 8 cannot be controlled by the provision of natural ventilation e.g. Work in enclosed areas, exposure should be controlled, where reasonably practicable, by the use of mechanical exhaust ventilation; when this is not reasonably practicable, suitable respiratory protective equipment must be worn.

**Hand protection:** When skin exposure may occur, advice should be sought from glove suppliers on appropriate types and usage times for this product. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

**Eye protection:** Eye protection designed to protect against liquid splashes should be worn.

**Skin protection:** Cotton or cotton/synthetic overalls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a recognised skin cleaner. Always wash your hands before eating, smoking or using the toilet.

## Section 9: Physical and chemical properties

Physical state	Viscous paste
Flash point	>100°C
Viscosity	N/A
Specific gravity	1.60-1.64 @ 20°C
Solubility in water	Miscible when wet
pH	7.7-8.5
VOC	3g/ltr
LEED(2009) VOC	3.5g/ltr

### Shelf life - 18 months

(Tubes must be stored between 5°C and 23°C in unopened condition) - Do not expose to frost.

## Section 10: Stability and reactivity

- 10.1 **Reactivity:** No data available
- 10.2 **Chemical stability:** Stable under normal temperature and storage conditions
- 10.3 **Possibility of hazardous reactions:** None known
- 10.4 **Conditions to avoid:** See section 10.3
- 10.5 **Incompatible materials:** See section 10.3
- 10.6 **Hazardous decomposition products:** Oxides of carbon released under high temperature (>300°C)

## Section 11: Toxicological information

- 11.1 Information on toxicological effects  
There is no evidence of toxicological effects of the product
- Ingestion:** May cause discomfort if swallowed. May cause stomach pain
- Skin contact:** May be irritating to skin
- Eye contact:** Risk of irritation to eyes.
- Sensitisation:** Not sensitising
- Stot:** Not classified

## Section 12: Ecological information

- 112.1 **Ecotoxicity:** Not regarded as dangerous for the environment, Not considered toxic to fish
- 12.2 **Persistence and degradability:** The product is not biodegradable
- 12.3 **Bio accumulative potential:** The product is not bio accumulating
- 12.4 **Mobility in soil:** Not mobile
- 12.5 **Results of pbt and vpvb assessment:** Not classified as pbt/vpvb
- 12.6 **Other adverse effects:** None known

## Section 13: Disposal considerations

Do not allow to enter drains or water courses. Wastes, including emptied containers, are controlled waste and should be disposed of in accordance with regulations made under the 'control of pollution act' and the 'environmental protection act'. Using information provided in this data sheet, advice should be obtained from the relevant environment agency whether the special waste regulations apply.

## Section 14: Transport information

**Transport within the users premises:** Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Onwards transport subsequent to purchase:** Transport to be in accordance with adr for road, imdg for sea and icao/iata for air.

**Proper shipping name:** The product is not classified as dangerous for carriage.

**Un number**

**Hazard class:**

**Packing group:**

**Sub-hazard class:**

## Section 15: Regulatory information

### 15.1 Safety, health and environmental regulations / Legislation specific for the substance or mixture

Control of substances hazardous to health regulations 2002  
 Environment act 1995  
 Management of health and safety at work regulations 1999  
 Personal protective equipment at work regulations 2002  
 Special waste regulations 1996 as amended

#### Health and safety executive guidance notes

HS(G)37 An introduction to local exhaust ventilation  
 EH40 Occupational exposure limits  
 EH44 Dust: general principles of protection  
 HS(G)53 The selection, use and maintenance of respiratory protective equipment  
 HS(G)71 Storage of packaged dangerous substances  
 HS(G)193 Coshh essentials: easy steps to control chemicals  
 I23 Manual handling guidance on regulations

#### British standards publications

EN420: General requirements for gloves  
 EN166: Personal eye protection: specifications  
 BS2092: Eye protection for industrial and non-industrial users  
 BS4275: Recommendations for the selection, use and maintenance of respiratory protective equipment

### 15.2 Chemical safety assessment

## Section 16: Other information

### Symbols and text of the H phrases in section 2 and 3:

**H412 Harmful to aquatic life with long lasting effects**

The information contained in the health and safety data sheet is provided in accordance with the requirements of eu regulation 1272/2008 (clp). The product should not be used for purposes other than those identified without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. This information contained in the safety data sheet is based on present knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular application.