

Pyroplex

Fire Rated Expanding Foam



750ml
Hand Held
PFRF750A



750ml
Gun Application
PFRF750GUN



Pyroplex Flame retardant based polyurethane expanding foam for sealing gaps around door frames or perimeter pointing. Expands up to 38 times its volume. Suitable for use on FD30, FD60, FD90 and FD120 doorsets. Pyroplex fire rated expanding foam will achieve a fire resistance period of up to 120 minutes.

Performance and Certification: Fire – BS EN 1366-4 | Certifire TS40 Certificate CF828

Test Standard

- Fire – BS EN 1366-4 | Certifire TS40 Certificate CF828

Features

- Fire resistance of up to 2 hours dependent upon gap to depth ratio.
- Quick curing, can be cut, sawn or formed within 60 minutes of application.
- Easy to install, with up to 3m linear joint being fitted in under 10 minutes.
- Can be painted and/or plastered without additional primers.
- Expands up to 38 times its volume.

Material

- Flame retardant based polyurethane.

Supplied

- 750ml Hand held and gun application.
- Available in pink foam.
Other colours are available on special request.

Application

Pyroplex Fire Rated Expanding Foam is suitable for use in a wide range of construction and building fire stopping solutions.

Health and safety

- Store between 5°C and 30°C in unopened condition
Do not expose to frost.
- Use in well ventilated areas